

productinformation

tesa® 88150

High temperature & high shear transfer tape

tesa® 88150 is a conformable, transparent, water-based acrylic transfer tape. The adhesive offers high temperature and high shear performance, and has been developed for lamination and converting applications.

Main features:

- Available in 60" / 1524mm usable width
- Conformable to difficult 3D shapes
- Good die cutting properties

Main Application

Lamination of flexible substrates

- NVH (noise, vibration, harshness) and BSR (buzz, squeak, rattle) materials
- Rubber materials for gaskets
- Plastics or vinyls for label and tag applications
- Decorative fabrics

Technical Data

▪ Backing material	none	▪ Colour of liner	white/blue logo
▪ Color	transparent	▪ Thickness of liner	106 µm
▪ Total thickness	127 µm	▪ Weight of liner	98 g/m ²
▪ Type of adhesive	water-based acrylic	▪ Temperature resistance from	-40 °C
▪ Type of liner	poly-coated paper	▪ Temperature resistance up to	200 °C

Adhesion to

▪ Steel (initial)	3.0 N/cm	▪ PC (after 3 days)	14.0 N/cm
▪ Steel (after 3 days)	8.0 N/cm	▪ PE (after 3 days)	1.5 N/cm
▪ Glass (after 3 days)	6.0 N/cm		

Properties

▪ Suitable for die cutting	yes	▪ Static shear resistance	●●●●
▪ Suitable for rough surfaces	●●●●	▪ Conformability	●●●●
▪ Tack	●●●		

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=88150>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

tesa® 88150

High temperature & high shear transfer tape

Additional Information

Also available as tesa® 88150 PV13.

- PET liner; 50.8µm thickness

For latest information on this product please visit <http://l.tesa.com/?ip=88150>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.